

SAFETY DATA SHEET

GLOBAL ASSEMBLY PASTE

10001 1.00 GB Current 10.07.97

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name GLOBAL Assembly Paste
Manufacturer/Supplier Global Lubricants Limited
Address 7 Sandwell Business Development Centre, Oldbury Rd,
Smethwick, West Midlands, B66 1NN, England.

Phone Number +44 (0) 121 544 3638
Fax Number +44 (0) 121 544 3638
Emergency Phone Number +44 (0) 410754382

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Preparation / Hazardous Components EEC Classification

Component No constituents need to be specified

3. HAZARD IDENTIFICATION

Main Hazards Not classified as hazardous.

Health Effects - Skin - Repeated and/or prolonged contact may lead to dermatitis.

4. FIRST AID MEASURES

First Aid - Eyes Wash out eye with plenty of water. Obtain medical attention if soreness or redness persists.

First Aid - Skin Wash skin with soap and water. If grease has been injected under the skin, seek medical advice immediately.

First Aid - Ingestion Do not induce vomiting. Obtain medical attention.

5. FIRE FIGHTING MEASURES

Use foam, dry chemical or carbon dioxide. Do not use water jet. This product may give rise to hazardous fumes in a fire. Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Material can create slippery conditions underfoot. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Handling When applying by grease gun, care must be taken not to inject this product under the skin.

Storage Storage temperature should be controlled to between 1 and 40 °C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Control Measures	No specific measures necessary.
Hand Protection	Use a good quality barrier cream.
Eye Protection	No specific measures necessary.
Body Protection	Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Paste.
Colour	Blue. - Black.
Odour	Odourless.
Melting Point (°C)	Melts above 100.
Flash Point (PMCC) (°C)	Exceeds 150
Solubility in Water	(Insoluble. kg/m3)
Density (kg/m3)	1.6. (measured as kg/litre)
Auto-flammability (°C)	Above 150.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to Avoid	No specific measures necessary.
Materials to Avoid	Strong oxidising agents.
Hazardous Decomposition	
Combustion Products	Will generate: smoke, possibly thick and choking, resulting in zero visibility. oxides of sulphur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity.
-----------------------	------------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product is insoluble in water. The product is poorly absorbed onto soils or sediments.
Persistence/ Degradability	The product is expected to be resistant to biodegradation.
Bio-accumulation	Product is not expected to bioaccumulate

13. DISPOSAL

Product Disposal	Incineration or landfill. Dispose of in accordance with all applicable local and national regulations.
Container Disposal	No specific measures necessary.

14. TRANSPORT INFORMATION

UN Class	Not classified.
ADR/RID - Class	Not classified.
IMDG – Class	Not classified.
IATA – Class	Not classified.

15. REGULATORY INFORMATION

R phrases	None.
S phrases	None.

16. OTHER INFORMATION

Product Use For industrial use only. Lubricant.
MSDS first issued 10.07.97
MSDS data revised

17. NATIONAL LEGISLATION

EC Legislation EC Directive 91/155/EEC defining the laying down and detailed arrangements laying down and detailed arrangements for the system of specific information relating to dangerous preparations. EC Directive 88/397/EEC relating to the classification, packaging and labelling of dangerous preparations.