

**SAFETY DATA SHEET**  
**ASSEMBLY SPRAY**  
**GB Current 02.08.1997**

SAFETY DATA SHEET Ref No. 10077

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Trade Name</b>	<b>GLOBAL ASSEMBLY SPRAY</b>
<b>Manufacturer/Supplier</b>	Global Lubricants Limited
<b>Address</b>	7 Sandwell Business Development Centre, Oldbury Rd, Smethwick, West Midlands, B66 1NN, England
<b>Phone Number</b>	+44 (0) 121 544 3638
<b>Fax Number</b>	+44 (0) 121 544 6505
<b>Emergency Phone Number</b>	+44 (0) 7710 754382

**2. COMPOSITION/INFORMATION ON THE COMPONENTS**

A blend of chlorinated hydrocarbon solvent(s), refined mineral oils(s), resin, Molybdenum disulphide and hydrocarbon propellants. For details of substances presenting a health hazard within the meaning of the Chemicals (Hazard Information & Packing) Regulations 1993 see under Section 8 of this Safety Data Sheet.

**3. HAZARD IDENTIFICATION**

Prolonged or repeated exposure to products containing refined mineral oil or HBPF distillates may result in dermatitis unless good personal hygiene is used. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame or any incandescent material. Deliberately concentrating and inhaling contents of this container is dangerous and can be fatal.

Extremely flammable

**4. FIRST AID MEASURES**

**General –**

In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**First Aid - Eyes**

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 mins holding the eyelids apart. Seek medical advice.

**First Aid - Skin**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. DO NOT use solvents or thinners.

**First Aid - Ingestion**

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

**First Aid - Inhalation**

Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

## **5. FIRE FIGHTING MEASURES**

### **Extinguishing Media**

Carbon dioxide, dry powder, Halogenated Hydrocarbons, sand, foam.

### **Unsuitable Extinguishing Media**

Do not use water.

### **Special Instructions for Fire-Fighting Personnel**

Fire will produce dense black smoke containing hazardous products of combustion (see section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water course.

## **6. ACCIDENTAL RELEASE MEASURES**

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in section 7 & 8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth and place in suitable container for disposal in accordance with the waste regulations. Do not allow large quantities to enter drains or water courses. If it does local water companies should be contacted.

## **7. HANDLING AND STORAGE**

Do not use in areas where potential sources of ignition exist. Electrical equipment should be protected to the appropriate standard. Use non sparking tools and exclude sources of heat, sparks and flames. Avoid skin and eye contact. For personal protection see section 8. Good housekeeping and regular removal of waste materials will minimise risks.

Store in accordance with the conditions of the licence which is necessary under the Petroleum (Consolidation) Act. See the HSE guidance note Storage of Flammable Liquids in Containers. Observe the label precautions. Store between 5 & 30°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. The principles contained in the HSE's guidance note Storage of Packaged Dangerous Substances should be observed when storing this product.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Engineering Control Measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If extraction methods are insufficient to maintain concentrations of particulates and/or solvent vapours below relevant OEL's, suitable respiratory protective equipment should be worn

Substance Name	% Conc Range	Symbol	OES 8hr ppm	OES 15 min ppm	Risk Phrases	Notation
Dichloromethane	>10% & = < 20%	Xn	100.00	300.00	40	MEL
Propane	>10% & = < 25%	F+			12	
COSHH keep Oxygen level > 18%						
BUTANE (1), ISOBUTANE (2)	>2.5% & = < 10%	F+	600.00	750.00	12	OES

#### **NOTES**

Notations = Sk – risk of absorption through skin Sen – respiratory sensitizer

Notations = Sk – risk of absorption through skin Sen – Respiratory sensitizer Bmgv – Biological Monitoring may be appropriate ( see Biological Monitoring Guidance Value in EH40 table 3)

OEL's are from EH40 except where marked SUP which are assigned by the supplier of the substance.

<b>General Protection</b>	All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.
<b>Respiratory Protection</b>	Air fed respiratory equipment should be worn when sprayed if levels cannot be controlled Below OEL's and engineering methods cannot be reasonably improved.
<b>Skin Protection</b>	Cotton or cotton/synthetic overalls or coveralls Are normally suitable. Grossly contaminated Clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.
<b>Eye Protection</b>	Eye protection designed to protect against liquid splashes should be worn.
<b>Hnad Protection</b>	Full physical protection is best. Seek relevant advise from glove manufacturers. Barrier cream may be of help but should not be applied after exposure has occurred.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State</b>	Dark grey liquid
<b>Flash Point (°C)</b>	<0°C Method Abel Apparatus to British Standards BS 2000 Pt.170
<b>Explosion Limits (%)</b>	
<b>Solubility in Water</b>	Immiscible
<b>Vapour Density</b>	Heavier than air
<b>Viscosity (cSt)</b>	
<b>Specific Gravity</b>	1.34 gms/cc method weight per gallon cup

## **10. STABILITY AND REACTIVITY**

Stable under the recommended storage and handling conditions (see Sect.7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and acid materials to prevent the possibility of an exothermic reaction.

## **11. TOXICOLOGICAL INFORMATION**

There is no data available on the product itself. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eye may cause irritation and reversible local damage.

## **12. ECOLOGICAL INFORMATION**

There is no data available on the product itself. Large quantities of the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

## **13. DISPOSAL**

Do not allow large quantities to enter the drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution & Environmental Protection Acts.

#### 14. TRANSPORT INFORMATION

Road/Rail	SI Number	1950	Class	2.2		
Sea	Marine Pollutant	No	UN Number	1950	Class	2.2
	Ems	2-13	MFAG	260***		
	Main Risk	Flammable				
	Shipping Name	Aerosol Dispensers Nos				

#### 15. REGULATORY INFORMATION

Classification	F+ Extremely flammable Xn - Harmful
Risk phrases	12 Extremely flammable. 40 Possible risk of irreversible effects
Safety phrases	2 Keep out of reach of children 46 If swallowed seek medical advice immediately and show Container or label. 26 In case of contact with eyes, rinse immediately with plenty of cold water and seek medical advice. 16 Keep away from sources of ignition – No smoking
P phrases	Do not breathe vapour or spray

The information contained in this Safety Data Sheet does not constitute the user's own assessment of The workplace risks as required by other Health & Safety legislation.  
The provision of the Health & Safety at Work Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

#### 16. OTHER INFORMATION

Text of any Risk Phrases listed in section 8	
R10	Flammable
R11	Highly flammable
R12	Extremely flammable
R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R36/37/38	Irritating to eyes, respiratory system and skin
R37	Irritating to the respiratory system
R38	Irritating to the skin
R40	Possible risk of irreversible effects
Product Use	For industrial use only. Lubricant.
MSDS first issued	02 August 1997
MSDS data revised	

## **17. NATIONAL LEGISLATION**

### **EC Legislation**

EC Directive 91/155/EEC defining the laying down and detailed arrangements for the system of specific information relating to dangerous preparations. EC Directive 88/379/EEC relating to the classification, packaging and labelling of dangerous preparations. EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of Member States relating to aerosol dispensers.

### **UK Guidance Publications**

EH40, Occupational Exposure Limits, HSE. Revised Annually.