

SAFETY DATA SHEET

GLOBAL ASSEMBLY SPRAY/ MOLY D SPRAY

Issued: 28 /04/ 2012

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: GLOBAL ASSEMBLY SPRAY/MOLY D SPRAY

Use / description of product: Aerosol. Extremely flammable.

Company name: Global Lubricants Ltd

13 Sandwell Business Development Centre

Oldbury Road, Smethwick, West Midlands, B66 1NN

England

Tel: +44 (0)121 5443638 Fax: +44 (0)121 5446505

E-mail:- admin@globallubricants.co.uk

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients:

- | | | | |
|------------------|--------|-----------------|-------------------|
| • PROPANE | 10-30% | CAS: 74-98-6 | EINECS: 200-827-9 |
| • BUTANE | 10-30% | CAS: 106-97-8 | EINECS: 203-448-7 |
| • PERCHLORETHANE | 2-4% | CAS: 64741-84-0 | EINECS: 204-825-9 |

Non-hazardous Ingredients

Mineral oil, Molybdenum disulphide and Resin

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to skin. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

Inhalation: Nausea and stomach pain may occur. There may be vomiting. Drowsiness or mental confusion may occur. There may be loss of consciousness.

SAFETY DATA SHEET

GLOBAL ASSEMBLY SPRAY/ MOLY D SPRAY

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give 1 pint of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide or Foam

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water. Do not use equipment in clean-up procedure which may produce sparks.

SAFETY DATA SHEET

GLOBAL ASSEMBLY SPRAY/ MOLY D SPRAY

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients:

- PROPANE/BUTANE L.T.E.L (8 hr exposure limit): 600 mg/m³ STEL (10 min exposure limit): 750 mg/m³
- PERCHLORETHANE L.T.E.L (8 hr exposure limit): 50 mg/m³ STEL (10 min exposure limit): 150 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Grey fluid

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flash point°C: -18

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Sources of ignition.

Materials to avoid: Oxidising agents.

Hazardous decomposition products: In combustion emits toxic fumes of carbon dioxide and carbon monoxide.

SAFETY DATA SHEET

GLOBAL ASSEMBLY SPRAY/ MOLY D SPRAY

11. TOXICOLOGICAL INFORMATION

Mammalian toxicity is considered to be moderate

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.

Persistence and degradability: Biodegradable in part only.

Bioaccumulative potential: No data available.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2 Item 10(b) 2

Labelling: 2.1

Shipping name: AEROSOLS

IMCO

UN no: 1950

Class: 9

IATA / ICAO

UN no: 1950 **Class:** 2 subsidiary risk 3 Packing Inst 203

Packing group II Trem Card 02

15. REGULATORY INFORMATION

Hazard symbols:



IRRITANT

Risk phrases:

R12: Extremely flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

SAFETY DATA SHEET

GLOBAL ASSEMBLY SPRAY/ MOLY D SPRAY

Safety phrases:

S9: Keep in well ventilated areas.

S16: Keep away from sources of ignition. No smoking.

S23: Do not breathe aerosol.

S25: Avoid contact with eyes.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

